



## Commercial Marine Dosing & Maintenance

Initial treatment of the large tanks or large treatment plants.

Tank Size	Dosing Quantity	Tank Size	Dosing Quantity
1000 Litres	1 Litre ProPower	4000 Litres	2.5 Litre ProPower
2000Litres	1.5 Litre ProPower	5000 Litres	3 Litre ProPower
3000 Litres	2 Litre ProPower	6000 Litres	3.5 Litre ProPower

Continued treatment for large tanks, dose after Pumping out. DO NOT FLUSH TANKS WITH WATER

Tank Size	Dosing Quantity	Tank Size	Dosing Quantity
1000 Litres	0.5 Litre ProPower	4000 Litres	1.5 Litre ProPower
2000Litres	0.75 Litre ProPower	5000 Litres	1.75 Litre ProPower
3000 Litres	1 Litre ProPower	6000 Litres	2 Litre ProPower

Weekly Dosing for Treatment Plants

Tank Size	Dosing Quantity	Tank Size	Dosing Quantity
1000 Litres	0.5 Litre ProPower	4000 Litres	1.5 Litre ProPower
2000Litres	0.75 Litre ProPower	5000 Litres	1.75 Litre ProPower
3000 Litres	1 Litre ProPower	6000 Litres	2 Litre ProPower

**METHOD:** Rock or shake container of ProPower, then add the required amount into a bucket, add a few litres of water and pour into each toilet on board till the bucket is empty. This allows the pipework to be treated between the toilet and the tanks, moving forward follow the same procedure, weekly for treatment plants.

**ALTERANATIVELY:** Rock or shake container of ProPower, then add the required amount into a bucket, add a few litres of water and pour into any toilet or directly into the tank, noting that some pipe work will not be treated.

## Weekly Dosing's for other Infrastructure

Use	Dosing Quantity	Method
Vacuum Toilets	20ml ProPower into a glass of water	Pour down toilet at the end of a day or trip with vacuum system off, flush, this allows the microbes to keep the line between the toilet and tank clean.
Drains	20ml ProPower into a glass of water	Pour down drains to rid petrification in S bends etc. Do this at the end of a day or trip
Waste Tank Breather Lines	50ml ProPower into 500ml of water	Pour / pump into breather line provided there is no carbon filter, otherwise dose below filter once per month.
Grey Tanks	As per previous tank schedule	

## What ProPower will achieve in your system

- Control Odour
- Control H<sub>2</sub>S (extending the life of steel tanks)
- Soften and remove crystalline deposits over time (the current condition of your pipes and tanks are an unknown)
- With continued use of ProPower the crystallisation will be stopped in most areas as your tanks ecology has now been modified changing the off gasses which previously caused that crystallisation.
- Sludge will be broken down regaining the full capacity of your tanks and/or increasing the efficiency of your waste plant.
- BOD (Biological Oxygen Demand) will be reduced thereby also increasing the efficiency of the system.

## Other Uses for ProPower on Board

- Dilute with water 1:10 for deodorisation of any organic smells, apply with a spray bottle
- Pour into drains 1:10 to clear smells
- Spray onto carpet of soiled material for cleaning and deodorization (always test for staining first)
- As per the initial dosing instructions for, ProPower is equally beneficial for your Grey Water Systems

## Do's & Don'ts

- Treat the system as a rural septic, do not clean with bleach and other heavily caustic chemicals
- Do not allow ProPower to freeze
- Do not store in direct sunlight
- ProPower is 100% Natural so there is not harm to human, animal or the environment!
- If ProPower is spilled simply wash with water.
- 

For more information, please refer to our website [www.probioticpower.com.au](http://www.probioticpower.com.au)

